

# 微電腦型RS-485顯示電錶(24X48mm/48x96mm) (MICROPROCESS RS-485 DISPLAY METER)(24X48mm/48x96mm)

MODEL  
MMX-RS



## ■特點(FEATURES)

- 5位數RS-485顯示電錶(5 digit RS-485 display meter)
- 顯示範圍-19999~99999位數(Readout range form -19999 to 99999 digit)
- 通訊協議Modbus RTU模式(Modbus RTU mode for RS-485 protocol)
- 寬範圍交直流兩用電源設計(Wide input range for auxiliary power)
- 尺寸小,穩定性高(Dimension small and High stability)

## 1. MODEL: MMX-RS- [ ] [ ] [ ] (選購型號)

NO	Display	NO	Case Size	NO	Aux. Power
1	One-display	1	24x48mm	A	AC/DC18~60V
2	Two-display	2	48x96mm	B	AC/DC90~260V
• Two-display only 48X96mm				• Less 3VA for AC/DC input	

## 2. SPECIFICATION (主要規格)

- Readout range : -19999~99999 digit  
(顯示範圍)
- RS-485 baud rate : 19200/9600/4800/2400 selective  
(傳輸速率)
- RS-485 address : "01"~"FF"(0~255)  
(通訊位址)
- RS-485 protocol : Modbus RTU mode  
(通訊協議)
- Display : Red high efficiency LEDs high 10.16 mm (0.4") (MMX-RS-11X)  
Red high efficiency LEDs high 20.32 mm (0.8") (MMX-RS-12X)  
Red high efficiency LEDs high 10.16 mm (0.4")x2 (MMX-RS-22X)  
(顯示幕)
- Parameter setting : Touch switches  
(參數設定方式)
- Memory mode : Non-volatile E<sup>2</sup> PROM memory  
(記憶方式)
- Dielectric strength : 2KVac/1 min. (input/power)  
(絕緣耐壓能力)
- Operating condition : 0~50°C (20 to 90% RH non-condensed)  
(使用環境條件)
- Storage condition : 0~70°C (20 to 90% RH non-condensed)  
(存放環境條件)
- CE EMC Certification : EN 55022:1998/A1:2000 Class A  
EN 61000-3-2:2000  
EN 61000-3-3:1995/A1:2001  
EN 55024:1998/A1:2001  
(CE認證)

## 3. OUTSIDE DIMENSION AND CONNECTION DIAGRAM (外型尺寸與開孔尺寸與配線圖)

